

# Family Correlated Photometric Data

The following photometric information is developed using correlated data. Finelite considers a family to be a group of luminaires where critical performance metrics such as photometric performance, thermal performance, and electrical performance can be accurately projected via a combination of LM79 tests at the luminaire level and well-documented specifications at the component level.

For more information, please download [Finelite's Family Correlated White Paper](#)

Additional links:

- [Solid-State Lighting: Early Lessons Learned on the Way to Market](#)  
(U.S. Department of Energy)
- [Lighting Facts®](#)
- [Design Lights Consortium®](#)

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : HP-4-P-D-4FT-B-8TW-DAO-ITL94331.902.IES**

**DESCRIPTION INFORMATION (From Photometric File)**

[TEST]ITL94331.902 Family Correlation File  
[TESTLAB]INDEPENDENT TESTING LABORATORIES, INC.  
[TESTDATE]01/11/21  
[ISSUE DATE]07/02/2021  
[MANUFAC]FINELITE, INC.  
[LUMCAT]HP-4-P-D-4ft-B-8TW-DAO  
[OTHER]ies file is based on 3500K; see luminaire tech sheet at [www.finelite.com](http://www.finelite.com)  
for lumen adjustment factors for other CCT's & CRI's  
[INPUT\_ELECTRICAL]120.0 VOLTS, 19.5 WATTS  
[INPUT\_ELECTRICAL]277.0 VOLTS, 20.3 WATTS  
[ABSOLUTE LUMENS]1999  
[OTHER]see [www.finelite.com](http://www.finelite.com) for source file ITL94331. For further details on Finelite family correlation files, go to  
[more][http://www.finelite.com/download\\_files/series\\_downloads/photometry\\_pdf/FL\\_Family\\_Correlation\\_WhitePaper.pdf](http://www.finelite.com/download_files/series_downloads/photometry_pdf/FL_Family_Correlation_WhitePaper.pdf)

**CHARACTERISTICS**

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	1999
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	102
Total Luminaire Watts	19.5
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.34
Spacing Criterion (90-270)	1.18
Spacing Criterion (Diagonal)	1.30
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.33 ft
Luminous Width (90-270)	4.00 ft
Luminous Height	0.00 ft

**LUMINANCE DATA (cd/sq.m)**

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	6077	6274	5200
55	5220	5580	4624
65	4370	4750	4031
75	3519	3894	3487
85	2758	3000	3048

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>	<u>112.5</u>	<u>135.0</u>	<u>157.5</u>	<u>180.0</u>
0.0	798.777	798.777	798.777	798.777	798.777	798.777	798.777	798.777	798.777
2.5	815.247	814.217	810.100	804.439	798.262	791.057	785.910	781.793	780.249
5.0	828.114	826.055	818.849	807.527	794.145	781.278	768.926	762.235	759.662
7.5	837.892	834.290	824.511	807.527	787.454	767.382	750.398	741.133	737.531
10.0	844.583	841.495	826.570	804.439	779.219	751.942	731.869	719.002	712.826
12.5	846.642	844.069	826.570	798.262	769.441	734.443	711.797	695.842	689.151
15.0	844.583	841.495	822.967	788.998	755.544	714.885	690.180	672.167	664.961
17.5	837.892	835.319	816.276	778.190	739.589	694.298	665.476	648.492	639.742
20.0	826.570	825.026	805.983	762.750	722.090	671.137	641.286	623.787	616.067
22.5	811.129	809.585	792.086	746.795	703.562	646.948	618.126	599.083	593.421
25.0	791.572	791.057	775.102	728.267	680.916	622.758	593.421	575.922	571.290
27.5	768.411	768.411	754.000	706.650	657.241	597.539	567.173	553.277	547.615
30.0	741.648	743.192	730.325	682.975	630.993	570.261	543.498	530.116	526.514
32.5	711.797	713.856	704.077	658.271	603.715	544.013	518.279	506.956	505.412
35.0	676.799	681.946	676.284	629.963	574.378	516.220	494.089	485.339	483.281
37.5	642.830	649.006	643.860	600.112	543.498	488.942	468.870	463.723	463.208
40.0	604.744	613.494	611.435	569.232	513.647	460.635	443.651	440.563	443.136
42.5	567.173	573.349	577.981	537.836	482.766	433.357	419.461	419.461	421.520
45.0	524.455	534.748	541.439	502.324	448.797	405.050	395.271	398.359	400.933
47.5	485.339	496.662	504.382	468.870	417.917	378.287	369.537	376.228	381.375
50.0	445.709	455.488	466.296	435.416	385.492	351.524	345.862	354.097	359.759
52.5	406.594	415.344	428.725	399.389	353.582	322.187	321.672	331.451	338.142
55.0	365.420	377.257	390.639	363.876	323.731	296.453	297.483	309.320	317.040
57.5	328.363	338.142	352.553	330.422	292.851	269.690	273.293	287.189	294.909
60.0	290.277	302.115	316.526	297.483	264.029	244.471	248.588	262.485	270.720
62.5	256.823	265.058	281.013	263.514	236.236	219.252	225.943	239.839	248.074
65.0	225.428	232.634	244.986	231.604	207.929	196.092	201.238	216.679	224.399
67.5	192.489	198.665	211.532	201.753	181.166	171.902	179.107	193.518	198.665
70.0	164.696	169.328	180.651	172.416	156.976	148.741	155.947	169.328	174.990
72.5	135.874	141.021	151.315	144.109	133.301	126.610	134.330	145.139	151.315
75.0	111.170	115.287	123.008	118.375	110.141	106.023	112.199	122.493	127.640
77.5	88.524	91.098	97.274	94.700	88.524	85.436	91.612	99.332	102.421
80.0	66.908	68.967	73.599	73.084	67.937	66.393	71.025	77.716	79.775
82.5	47.350	47.865	51.468	50.953	49.409	48.380	51.468	55.585	57.644
85.0	29.337	29.337	31.910	31.910	32.425	30.881	32.939	34.483	36.027
87.5	11.323	12.352	13.382	14.411	14.926	14.411	14.926	15.440	15.955
90.0	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000

**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : HP-4-P-D-4FT-B-8TW-DAO-ITL94331.902.IES**

**ZONAL LUMEN SUMMARY**

Zone	Lumens	%Lamp	%Fixt
0-20	288.05	N.A.	14.40
0-30	601.44	N.A.	30.10
0-40	963.80	N.A.	48.20
0-60	1621.64	N.A.	81.10
0-80	1962.58	N.A.	98.20
0-90	1998.75	N.A.	100.00
10-90	1923.43	N.A.	96.20
20-40	675.76	N.A.	33.80
20-50	1031.65	N.A.	51.60
40-70	875.58	N.A.	43.80
60-80	340.93	N.A.	17.10
70-80	123.20	N.A.	6.20
80-90	36.17	N.A.	1.80
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	1998.75	N.A.	100.00

Total Luminaire Efficiency = N.A. %

**ZONAL LUMEN SUMMARY**

Zone	Lumens
0-10	75.32
10-20	212.73
20-30	313.39
30-40	362.37
40-50	355.90
50-60	301.94
60-70	217.74
70-80	123.20
80-90	36.17
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


**IES INDOOR REPORT**  
**PHOTOMETRIC FILENAME : HP-4-P-D-4FT-B-8TW-DAO-ITL94331.902.IES**

**COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD**

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	100	97	106	102	98	95	98	95	92	94	92	89	90	88	87	84
2	100	92	85	79	97	90	84	78	86	81	77	83	79	75	80	76	73	71
3	91	81	73	66	89	79	72	66	76	70	65	73	68	64	71	66	63	60
4	84	72	63	57	81	71	63	56	68	61	56	66	60	55	64	58	54	52
5	77	64	56	49	75	63	55	49	61	54	48	59	53	48	57	52	47	45
6	71	58	49	43	69	57	49	43	55	48	43	54	47	42	52	46	42	40
7	66	53	44	38	64	52	44	38	51	43	38	49	43	38	48	42	37	35
8	62	48	40	34	60	48	40	34	46	39	34	45	39	34	44	38	34	32
9	58	45	36	31	56	44	36	31	43	36	31	42	35	31	41	35	30	29
10	54	41	33	28	53	41	33	28	40	33	28	39	32	28	38	32	28	26

POLAR GRAPH



Maximum Candela = 846.642 Located At Horizontal Angle = 0, Vertical Angle = 12.5  
# 1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)