



FINELITE

Series 10 Instructions Fully Adjustable Cable




1. Position the adjustable cable gripper over the Level and Lock™ Assembly, turn to engage threads. Move slider for side to side leveling. Lock by turning cable gripper securely until serrated keps nut fits tightly against slider.




2. Unscrew release lock nut and depress to adjust cable height, turn to lock. Slide Safety Stop and Safety Crimp up cable to within 9" of cable gripper. Secure Safety Crimp with crimping tool. Trim excess cable. Lower Safety Stop, Safety Crimp and 9" of cable into fixture.

INSERT TO COMPLETE (joint detail)




FINAL CHECK: In completed installation Release Lock Nut is screwed down, serrated keps nut is tight against slider, crimp has been secured, Safety Stop and Safety Crimp and 9" of aircraft cable are securely inside fixture body.

89449 S10 Fully Adjustable Cable Installation Instructions



ADJUSTABLE CABLE GRIPPER ASSEMBLY



INSTALLATION DIRECTIONS SERIES 10

1. Position the adjustable cable gripper over the Level and Lock™ Assembly, turn to engage threads.
2. Move slider for side to side leveling. Lock by turning cable gripper securely until serrated keps nut fits tightly against slider.
3. Unscrew Release Lock Nut and depress threaded shaft to adjust cable height. Screw down Release Lock Nut. Pull excess A/C away from fixture.
4. Pull all but 9" of cable up through Safety Stop and Safety Crimp.
5. Secure Safety Crimp with crimping tool. Trim off excess cable.
6. Push Safety Stop, Safety Crimp and remaining 9" of cable down into fixture body.

89449 S10 Fully Adjustable Cable Assembly