

	Finelite FineTune Driver With FineTune Controls	Pre-Qualified DMX Drivers with FineTune Controls	Pre-Qualified DMX Drivers with Controls by others	Pre-Qualified DALI Drivers with Controls by others	Pre-Qualified PoE Systems with Controls by others	Pre-Qualified Lutron Drivers with Controls by others
Design Features Options						
Color Temperature (CCT) Range: 2700K - 6500K	✓	✓	✓	✓	✓	✓
CRI 80+ & 90+	✓	✓	✓	✓	✓	✓
Tailored Lengths ¹	✓			✓		✓
Tailored Angles (corners) ²	✓			✓		✓
Tailored Outputs ³	B & V Only	✓	✓	✓		✓
Controls provided by Finelite	✓	✓				
Controls provided by Others			✓	✓	✓	✓
Pre-Wired Plug-Together Wiring	✓	✓				
DMX Signal Repeater Gateway Required		✓	✓			
Daylight Sensors (plug-and-play)	✓	✓				
Occupancy Sensor (plug-and-play)	✓	✓				
Fixture Integrated Sensors						
Factory-installed Battery Pack	✓	✓	✓	✓		✓
Factory-installed GTD				✓		✓
EM/Gen				✓		✓
Nightlight						
10-Year Warranty	✓					✓
5-Year Warranty		✓	✓	✓	✓	
10-working day lead-time for standard options ⁴	✓					
Factory Pre-Check required prior to order ⁵	✓	✓	✓	✓	✓	✓
Available in Canada	✓	✓	✓	✓	✓	✓

E1, S11 LED Micro Flex, Muro, and PLS are not available with Tunable White.

NOTE:

1. Minimum 2', increments accurate to 1/16th" (± 1/32").
2. Illuminated 90° corners in a single plane, standard.
3. Four (4) standard light output options - S, B, H, & V.
4. Lead-time starts the day after the order is finalized and Pre-Check is confirmed.
5. All controls systems projects must be checked by Finelite application specialists.
Non-qualified drivers can be evaluated for integration.