

Product Photometry and ies files are also available online at www.finelite.com.
For layouts or additional photometry, contact your local representative or the factory.


S15: 1 T8




EFFICIENCY = 73.4%

80% Uplight
20% Downlight

(LSI Report 18056)



CANDELA DISTRIBUTION		FLUX		
0.0	22.5	45.0	67.5	90.0
0	168	168	168	168
5	166	167	167	167
15	159	160	161	161
25	144	146	149	152
35	122	126	131	134
45	95	98	105	108
55	63	67	74	76
65	31	34	40	44
75	10	14	18	22
85	1	4	13	22
90	0	0	0	0
95	19	131	225	274
105	67	212	367	476
115	121	194	351	459
125	170	207	289	386
135	212	232	276	320
145	244	257	282	303
155	270	274	287	298
165	286	287	292	294
175	294	293	294	292
180	293	293	293	293



ZONAL LUMEN SUMMARY			
ZONE	LUMENS	%LAMP	%FIXT
0-30	129	4.33	5.90
0-40	210	7.02	9.56
0-60	353	11.80	16.07
0-90	432	14.21	19.63
40-90	221	7.39	10.07
60-90	78	2.61	3.56
90-180	1769	58.99	80.37
0-180	2201	73.39	100.00


S15: 2 T8




EFFICIENCY = 71.2%

78% Uplight
22% Downlight

(LSI Report 18057)



CANDELA DISTRIBUTION		FLUX		
0.0	22.5	45.0	67.5	90.0
0	382	382	382	382
5	378	379	380	381
15	361	363	366	367
25	326	330	335	340
35	277	284	292	299
45	213	220	233	240
55	139	149	164	173
65	68	76	95	101
75	21	30	41	46
85	2	9	24	44
90	0	0	0	0
95	28	186	291	357
105	123	365	570	705
115	232	395	647	788
125	336	442	628	786
135	423	495	623	733
145	495	538	628	693
155	548	567	619	661
165	584	589	609	625
175	603	602	604	601
180	603	603	603	603



ZONAL LUMEN SUMMARY			
ZONE	LUMENS	%LAMP	%FIXT
0-30	293	4.89	6.86
0-40	474	7.90	11.10
0-60	794	13.25	18.60
0-90	961	16.02	22.49
40-90	487	8.12	11.39
60-90	166	2.77	3.89
90-180	3312	55.22	77.51
0-180	4274	71.24	100.00


S15: 1 T5HO



EFFICIENCY = 81.9%

75% Uplight
25% Downlight

(LSI Report 18033)



CANDELA DISTRIBUTION		FLUX		
0.0	22.5	45	67.5	90
0	371	371	371	371
5	369	370	370	370
15	348	349	353	354
25	310	313	317	324
35	259	265	272	279
45	197	202	214	218
55	129	136	149	156
65	69	75	87	93
75	29	34	42	47
85	3	11	33	47
90	0	0	0	0
95	24	209	493	651
105	100	338	480	653
115	182	333	531	604
125	257	329	486	600
135	320	356	447	530
145	369	389	435	480
155	405	412	435	454
165	428	429	437	442
175	442	438	439	437
180	439	439	439	439



ZONAL LUMEN SUMMARY			
ZONE	LUMENS	%LAMP	%FIXT
0-30	280	6.24	7.61
0-40	449	9.99	12.19
0-60	741	16.48	20.12
0-90	919	20.44	24.96
40-90	470	10.46	12.77
60-90	178	3.96	4.84
90-180	2766	61.47	75.04
0-180	3686	81.92	100.00


S15: 2 T5HO



EFFICIENCY = 77.6%

76% Uplight
24% Downlight

(LSI Report 18100)



CANDELA DISTRIBUTION		FLUX		
0.0	22.5	45	67.5	90
0	692	692	692	692
5	689	689	688	684
15	652	652	654	655
25	579	584	591	596
35	482	491	503	512
45	366	376	393	404
55	239	251	273	289
65	127	139	161	176
75	53	61	77	89
85	5	19	53	110
90	0	0	0	0
95	45	361	707	823
105	187	627	1062	1240
115	341	620	1096	1389
125	481	637	960	1246
135	600	691	874	1055
145	696	746	848	950
155	766	786	838	883
165	813	817	834	845
175	835	833	833	828
180	832	832	832	832



ZONAL LUMEN SUMMARY			
ZONE	LUMENS	%LAMP	%FIXT
0-30	521	5.79	7.46
0-40	833	9.26	11.93
0-60	1375	15.28	19.69
0-90	1695	18.84	24.28
40-90	862	9.58	12.34
60-90	320	3.56	4.58
90-180	5289	58.77	75.72
0-180	6984	77.61	100.00