



The Curve defines. The Curve adapts. The Curve creates. The Curve by *Finelite™* shapes light for efficient and flexible work environments.







Best in Class Top-Ranked Winner

- Full Range dimming to 5%
- Delivers 49 lumens per watt
- 363 total lumens
- LM-79 and LM-80 data available
- State of the art LED array

•

- Buy America Act of 2009 compliant
- 5-year, worry-free warranty





Sustainable Materials

Reclaimed steel perforations from our linear indirect luminaires are used to create the weight for the base. Turn the base over to see for yourself.

Visible Difference

- Delivers 49 lumens per watt
- Consumes just 8 watts of power
- Buy America Act of 2009 compliant
- Up to 30 years life with typical office use
- Wide uniform coverage on the desk surface
- Research supports over 50% energy savings in offices
- Research from the Emerging Technologies Coordinating Council confirms workers prefer this type of lighting. They are more satisfied and comfortable in this type of environment.
- Best-in-industry thermal management
- State of the art LED array Contact factory for current specification



Curve components are constructed from zinc, steel, electronics, aluminum and plastic. Curve is 97% recyclable at the end of useful life.



97% Recycled Content



For more environmental product data, visit www.finelite.com.





BEST IN CLASS LED TECHNOLOGY combined with best-practice office lighting...It adjusts to you.

Beyond

Technical Specifications

- Power consumption: 8W max.
- Light output: 363 lumens
- Efficacy: 49 lumens per watt
- Color temperature: 3500K
- Color rendering: 82 CRI
- L₇₀: Rated for 100,000 hours to 70% of initial lumens*
- QuickTouch™ dimming to 5%
- Zero power used when power supply is turned off
- LM-79 tested and LM-80 data available
- Complies with FCC requirements for commercial and residential use
- Backed by 5-year, worry-free warranty
- Field-replaceable LED module

* L₇₀ lifetime is estimated by the LED manufacturer based on independent testing of the Curve luminaire.

Style Elements

- Ultra-sleek profile
- Silver powder coat textured finish; custom colors available upon request

PLS System Compatibility

- Fully integrates with PLS System solution
- Seamless expansion for existing projects

Ordering Information

- Lamp: DL-C-S
- Base: Weighted WBC-S, Clamp CL-S, Mounting Plate MP-S
- Finish: Silver standard. 188 RAL colors available.
- Power Supply: PS-8W






30500 Whipple Rd • Union City, CA 94587-1530 • 510-441-1100 • Fax: 510-441-1510 • www.finelite.com Photography Credits: © Michael David Rose Photography - Product. ©2012 Finelite Inc. All rights reserved. CP10037 06/12

Curve Photometric Performance

 The entire task area is illuminated with a single desk lamp.



Initial illuminance values in footcandles calculated using LM-79 photometric report. Lamp head is 16" above desk surface at full light output.