





and sustainable work areas that allow for true occupant control.

LIGHT ENGINE

Edge uses mid-powered LEDs spaced uniformly for even distribution on the task plane.



EVEN GLOW DIFFUSER

Edge's Even Glow diffuser covers the LEDs for improved distribution, minimizes multiple shadow effects, and is easy to clean for applications requiring periodic wipe down.



FULL RANGE, ON-BOARD DIMMING TO OFF


Edge comes equipped with individual dimming to off on each luminaire.

21W & 60W



POWER SUPPLIES:

The power supply draws no power during offstate. Available with 8W, 21W or 60W power supplies to meet a variety of application needs.



ORDERING GUIDE Sample Number: UC-E – 22"– S – PS-21W – OCC	UC-E
Lamp (UC-E)	
Length (12", 22", 45")†	
Finish (Silver)	
Power Supply (PS-8W*, PS-21W, PS-60W)	
Occupancy Sensor (OCC)**	
ENERGY STAR* (ES1 ES2)	


- [†] 45" can use 21W or 60W power supply. * Edge is ENERGY STAR[®] qualified when using two 12" units (ES1) or one 22" (ES2) unit on an 8W power supply. ** OCC sensor available for PS-21W & PS-60W only.

Finelite, Inc. • 30500 Whipple Road • Union City, CA 94587-1530 • 510 / 441-1100 • Fax: 510 / 441-1510 • www.finelite.com



Edge by Finelite

LENGTHS: 12", 22", and 45"* (nominal). 45.25" 12.25"




Actual Size



TECHNICAL SPECIFICATIONS

- · Buy American Act of 2009 Compliant
- Efficacy (Lumens per Watt): 45": 62.2* / 22": 62.2 / 12": 48.9
- Light Output (Lumens): 45": 760* / 22": 380 / 12": 196
- Power Consumption: 45": 12.2W* / 22": 6.1W / 12": 4W
- Color Temperature: 3500K
- Color Rendering (CRI): 87
- R9 Value: 22": 32 / 12": 34
- L₉₀: Rated for 100,000 hours to 90% of initial lumens**
- LM-79 tested and LM-80 data is available
- Complies with FCC requirements for commercial and residential use
- Compatible with Personal Lighting System (PLS)
- End of life statement: 86% recyclable at the end of its useful life
- ETL Listed
- · RoHS Compliant
- * 45" performance is projected.
- ** L_{90} lifetime is estimated by the LED manufacturer based on independent testing of the Edge luminaire.



CABLE MANAGEMENT HARDWARE

For best results, clean magnet or cabinet surface with isopropyl alcohol before applying adhesive clip.










PHOTOMETRIC PERFORMANCE

Superior lateral throw provides proper illumination over a wide area. Example below: 22" unit installed on a 4 ft. binder bin.




One 22" Edge provides ample illumination beneath a 4 ft. binder area. For additional output specify a 45" luminaire rather than two 22" luminaires.

CABLES

Edge by Finelite comes standard with (1) 12' power cable and cable management hardware.

Power Cables



Cat No. CPNC-12

[12' Power Cable]

Patch Cables



Daisy chains two male 1.3mm jacks.
Cat No. CP-3 [3" Patch Cable]
Cat No. CP-6 [6" Patch Cable]

Cat No. CP-6 [6" Patch Cable]
Cat No. CP-14 [14" Patch Cable]
Cat No. CP-28 [28" Patch Cable]


Splitter Cable



Cat No. CY-6

[6" Splitter Cable]

Extension Cable



Cat No. CX-8

[8 ft. Extension Cable]