

## **Disassembly Instructions**

S12 LED 3E and 4E breaks down easily for recycling at the end of usable life.

| Reflectors    | 4 <u>n n n n n n n n n n n n n n n n n n n </u> | Ballast Channels 🕞 |   | ······································ | , |
|---------------|---|--------------------|---|--|---|
| Top Reflector |   | Saddle Brackets    |   |  |   |
| Drivers       |   |                    |   |  |   |
| LED Array     |   | Housing            |   | •                                      |   |
| Diffuser      |   | Endcaps            |   | Wiring                                 |   |
|               |   |                    |   |  |   |
| Č             | STEEL   | Û.                 | ڏ |  |   |

\* Recycling information typical for all luminaire sizes. Contact factory for more information.



Patent Pending

## S12 LED 3E & 4E Environmental SProduct Summary



S12 LED 3E and 4E data shown

| 100% recyclable  | 100% recycled content  |  |  |
|--|--|--|--|
| S12 LED 3E and 4E components are constructed from steel, E-Waste, aluminum, acrylic plastic, and copper. S12 LED 3E and 4E is 100% recyclable at the end of useful life. | S12 LED 3E and 4E is comprised of 100% recycled materials.       |  |  |
| 3%<br>4<br>13%<br>74   | Steel =<br>E-Waste =<br>Aluminum =<br>Plastic =<br>Copper Wire = |  |  |