

## WELL & LEED Compatible Finelite Products

Fixture	Luminaire Construction	Red List Declared	Red List Approved	Red List Free	Downlight Meets Well Building Feature L04 Option 1 c		Downlight Meets LEED v4.1 Glare Control	
					Requirements at 80CRI	Requirements at 90CRI	Requirements at 80CRI	Requirements at 90CRI
E1	Steel	✓	Pending	Pending	N/A	N/A	N/A	N/A
E2	Aluminum	✓	Pending	Pending	Tailored to 371 lumens/ft	S/B	S	S/B
E3	Aluminum	✓	✓	Pending	N/A	N/A	N/A	N/A
HO4	Aluminum	✓	✓	Pending	S	S/B	S/B	S/B
HP-WG	Steel	✓	✓	Pending	N/A	N/A	N/A	N/A
HP-WS	Steel	✓	✓	Pending	N/A	N/A	N/A	N/A
HP-2 Acoustic	Polyester Fiber	✓	✓	✓ **	Tailored to 296 lumens/ft	S	S	S
HP-2 DCO	Aluminum	✓	✓	Pending	Tailored to 296 lumens/ft	S	S	S/B
HP-2 Micro Louver White	Aluminum	✓	✓	Pending	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
HP-2 Micro Louver Black	Aluminum	✓	✓	Pending	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
HP-2 RG LHE	Aluminum	✓	✓	Pending	S/B/H	S/B/H/V	S/B/H	S/B/H/V
HP-2 RG LHC	Aluminum	✓	✓	Pending	S	S/B	S/B/H	S/B/H/V
HP-2 Drop Lens	Aluminum	✓	✓	Pending	S	S/B	S	S/B
HP-2 RG WCB	Aluminum	✓	✓	Pending	S	S/B	S/B	S/B
HP-2 DSO	Aluminum	✓	✓	Pending	Tailored to 274 lumens/ft	S	Tailored to 274 lumens/ft	S
HP-2 Circle	Steel	✓	✓	Pending	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
HP-2 WS	Steel	✓	✓	Pending	N/A	N/A	N/A	N/A
HP-3	Aluminum	✓	✓	Pending	Tailored to 417 lumens/ft	S	S	S
HP-4 F	Aluminum	✓	✓	Pending	S/B	S/B/H	S/B	S/B/H
HP-4 LHE	Aluminum	✓	✓	Pending	S/B	S/B/H	S/B/H	S/B/H/V
HP-4 DSO	Aluminum	✓	✓	Pending	S	S/B	S/B	S/B/H
HP-4 RG	Aluminum	✓	✓	Pending	S/B	S/B	S/B	S/B/H
HP-4 DL	Aluminum	✓	✓	Pending	S/B	S/B/H	S/B/H	S/B/H/V
HP-4 LHC	Aluminum	✓	✓	Pending	S/B	S/B/H	S/B	S/B/H/V
HP-4 WCB	Aluminum	✓	✓	Pending	S/B	S/B	S/B	S/B/H
HP-4 Circle	Steel	✓	✓	Pending	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
HP-4 WL	Aluminum	Pending	Pending	Pending	S/B	S/B/H	S/B	S/B/H
HP-6	Aluminum	✓	✓	Pending	S/B/H	S/B/H/V	S/B/H	S/B/H/V
HPO	Aluminum	✓	✓	Pending	Tailored to 349 lumens/ft	S	S	S/B
HPR	Steel	✓	✓	Pending	S/B/H	S/B/H/V	S/B/H	S/B/H/V
HPT	Steel	✓	✓	Pending	S/B/H	S/B/H/V	S/B/H/V	S/B/H/V
HPW	Steel	✓	✓	Pending	N/A	N/A	N/A	N/A
HPX	Aluminum	✓	✓	Pending	Tailored to 340 lumens/ft	S	Tailored to 408 lumens/ft	S/B
S11 MF	Steel	✓	✓	Pending	N/A	N/A	N/A	N/A
S11 MP	Steel	✓	✓	Pending	N/A	N/A	N/A	N/A
S12	Steel	✓	✓	Pending	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
S16	Steel	✓	✓	Pending	S/B/H	S/B/H/V	S/B/H	S/B/H/V
S17	Steel	✓	✓	Pending	N/A	N/A	N/A	N/A
S18	Steel	✓	✓	Pending	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V
S19	Aluminum	✓	✓	Pending	S/B/H/V	S/B/H/V	S/B/H/V	S/B/H/V

\*\* HP-2 Acoustic Baffle Unlit is Red List Free.

Flicker: Our luminaires follow the recommendations outlined in IEEE Std. 1789-2015 and used components operate with a modulation frequency higher than 1250Hz under all dimming conditions. The components operate in the IEEE "NOEL" (No Observable Effect Level) specification range at all times.